



CNA584U

RCCB 1P+N 100A 100mA A S

Technical Characteristics

Architecture

| | |
|------------------|-------------------------------|
| Neutral position | right |
| Number of poles | 2 P |
| Type of pole | 1P+N |
| Fixing mode | DIN rail type O (symmetrical) |

Main electrical features

| | |
|------------------------------|-------|
| Rated operational voltage Ue | 230 V |
| Frequency | 50 Hz |
| Rated current | 100 A |
| Type of supply voltage | AC |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 500 V |
| Max operating voltage | 253 V |
| Rated impulse withstand voltage | 4000 V |

Electric current

| | |
|---|--------|
| Rated residual operating current | 100 mA |
| Rated conditional short-circuit current Inc according to EN 61008-1 | 10 kA |

Electric current / temperature

| | |
|---------------------|-------|
| Rating current 30°C | 100 A |
|---------------------|-------|

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 70 mm |
| Height of installed product | 85 mm |
| Width of installed product | 36 mm |

Power

| | |
|---------------------------|---------|
| Total power loss under IN | 13.89 W |
|---------------------------|---------|

Tripping

| | |
|-----------------------------|-----|
| Short-time delayed tripping | Yes |
|-----------------------------|-----|

Endurance

| | |
|--|-------|
| Electric endurance in number of cycles | 10000 |
| Number of mechanical operations | 20000 |

Capacity

| | |
|-------------------|---|
| Number of modules | 2 |
|-------------------|---|

Equipment

| | |
|---------------------|-----|
| Quick connect | no |
| Can be accessorized | Yes |

Standards

| | |
|---------------|------------|
| Standard text | EN 61008-1 |
|---------------|------------|

| | |
|-------------------------|-----------|
| European directive WEEE | concerned |
| Safety | |
| Protection index IP | IP20 |
| Residual current type | A SEL |