




Product Description: M-Lite™ IP67 Stainless Steel Marker Light


The M-Lite™ 2W LED marker light is discreet and small in size yet powerful, making this product perfectly suited for low level or ground lighting. Ideal to light up pathways, decking areas, patios and plinth lighting.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type |
|------------|---------|--------|--------|-------------|------------|-----------------|--------------|
| EN-ML1/30 | 2 | 3000 | 70 | 35 | 25 | Stainless Steel | Non Dimmable |
| EN-ML1/40 | 2 | 4000 | 75 | 38 | 25 | Stainless Steel | Non Dimmable |
| EN-ML1/BLU | 2 | | 17 | 9 | 25 | Stainless Steel | Non Dimmable |


Line Drawing



Polar Curve



Colour



Stainless Steel

Product Features:

- 240V Mains voltage 304 stainless steel LED marker light
- IP67 rated - ideal for both interior & exterior applications
- Available in warm white (3000K), cool white (4000K) and blue
- Pre-wired with 600mm of cable
- Supplied with mounting sleeve for in-ground installation
- Cut-out 35mm without mounting sleeve
- Cut-out 40mm with mounting sleeve
- 1.5kV surge protection
- 1 Year Warranty

Product Specs:

| | | | |
|--------------------------|-------------|--------------------------|-------|
| Input Voltage | 100~240V AC | Power Factor | 0.46 |
| IP Rating | IP67 | Lifetime L70 (hrs) | 30000 |
| IK Rating | IK06 | Lamp Base | Other |
| Length (mm) | 78 | Overall Diameter (mm) | 42 |
| Weight (Kg) | 0.249 | Height (mm) | 100 |
| Product Type | Markers | Cutout Diameter (mm) | 35-40 |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 60°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.