





Product Description:

LinearPac™ 1200mm 24W IP66 Anti-Corrosive

The IP66 LinearPac™ LED anti-corrosive provides up to 50% energy savings compared to traditional fluorescent. A highly efficient solution for both interior and exterior applications, it is designed for car parks, service areas, warehouses or retail environments.

| | | | | | | | 3113 17 |
|--|----|---|------|-----|--------|------|--------------|
| EN-ANT1224/40 | 24 | 4000 | 2760 | 115 | 120 | Grey | Non Dimmable |
| | | | | | | | |
| Line Drawing | | Polar Cu | urve | | Colour | | |
| H. T. C. | | 100 100 100 100 100 100 100 100 100 100 | 1207 | | Grey | | |

Feature & Benefits

- Multiple BESA mounting points (matches traditional fluorescent)
- Drop down gear tray for ease of installation and maintenance
- 20mm conduit entry at both ends and at the rear
- Stainless steel anti-tamper clips
- Fully polycarbonate opal diffuser and base
- IP66 rated
- 2x IP66 rated cable glands supplied
- IK10 rated
- -10° to +50° ambient operating temperature
- Plug & play emergency pack available (EN-ANTEM1)
- Plug & play emergency self-test pack available (EN-ANTEMST1)
- Plug & play microwave sensor available (EN-ANTMS1)
- 5 Year Warranty

Product Specs:

| Input Voltage | 220~240V AC | | |
|--------------------------|-------------|--|--|
| Power Factor | 0.90 | | |
| Lifetime L70 (hrs) | 50000hrs | | |
| Lamp Base | None | | |
| Length (mm) | 1200 | | |
| Height (mm) | 72 | | |
| Operating Temp. (Min) °C | -10°C | | |

| Input Frequency | 50/60HZ | | |
|--------------------------|---------|--|--|
| IP Rating | IP66 | | |
| IK Rating | IK10 | | |
| Width (mm) | 80 | | |
| Weight (Kg) | 1.216 | | |
| Product Type | Linears | | |
| Operating Temp. (Max) °C | 50°C | | |

Compliance & Approvals:























This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.