





Product Description:

Utilite™CS 15W Colour Switchable IP65 Oval Utility Bulkhead


Utilite™CS oval bulkhead has impact resistant polycarbonate housing, providing a tough exterior and making them ideal for all basic industrial, commercial and residential installations. Separate eyelid and grille bezels are available. The range also features colour switchable technology allowing the colour temperature to be set at either 3000K. 4000K or 6500K on site.


SKU Code	Wattage	ColorTemp	Lumens	BeamAngle	SKUType	FinishColor
AU-BH215CS	15	3000K	1500	120	Non Dimmable	White
AU-BH215CS	15	4000K	1650	120	Non Dimmable	White
AU-BH215CS	15	6500K	1550	120	Non Dimmable	White

Line Drawing

Polar Curve

Colour





Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Polycarbonate body and diffuser
- IP65 rated
- IK06 rated

-20° - +40° ambient operating
3 Year Warranty temperature

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.5
Lifetime L70 (hrs)	25000hrs
Lamp Base	None
Length (mm)	215
Projection (mm)	62
Product Type	Bulkheads
Operating Temp. (Max) °C	40°C

Input Frequency	50/60HZ
IP Rating	IP65
IK Rating	IK06
Width (mm)	115
Weight (Kg)	0.211
Height (mm)	62
Operating Temp. (Min) °C	-20°C

Compliance & Approvals:







Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.