




Product Description: Utilite[™]CS 20W Colour Switchable IP65 Oval Utility Bulkhead


Utilite[™]CS oval bulkhead has impact resistant polycarbonate housing, providing a tough exterior and making them ideal for all basic industrial, commercial and residential installations. Separate eyelid and grille bezels are available. The range also features colour switchable technology allowing the colour temperature to be set at either 3000K, 4000K or 6500K on site.

SKU Code	Wattage	ColorTemp	Lumens	BeamAngle	SKUType	FinishColor
AU-BH220CS	20	3000K	2050	120	Non Dimmable	White
AU-BH220CS	20	4000K	2300	120	Non Dimmable	White
AU-BH220CS	20	6400K	2100	120	Non Dimmable	White

Line Drawing



Polar Curve



Colour

Feature & Benefits

- Colour switchable between 3000K, 4000K and 6500K
- Polycarbonate body and diffuser
- IP65 rated
- IK06 rated
- -20° - +40° ambient operating temperature
- 3 Year Warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.5	IP Rating	IP65
Lifetime L70 (hrs)	25000hrs	IK Rating	IK06
Lamp Base	None	Width (mm)	146
Length (mm)	271	Weight (Kg)	0.321
Projection (mm)	76	Height (mm)	76
Product Type	Bulkheads	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.