

SpryteCS™

Colour Switchable Fixed / Adjustable Polycarbonate Downlights



- Colour switchable between 3000K/4000K/6500K
- ThermoTec™ heat management technology
- Sparkling low glare multifaceted lens
- Pre-wired with 500mm of 2 core cable
- Supplied with integrated driver

Technical Specifications

- Supply Voltage: 220-240 AC
- Lifespan: L70 40,000hrs
- Operating Temperature: -20°C / 40°C
- Body: Polycarbonate
- Diffuser: Polycarbonate
- Warranty: 5 Years



AU-DDL1019CS Supplied with interchangeable Round and Square Bezels

	Cat No.	Type	Watts (W)	Colour Temp. (K)	Lumens (lm)	Lm/W	Beam (°)	Cutout (mm)	Size (mm)	Finish
Fixed	AU-DL10160CS	Non Dim	6	3000 / 4000 / 6500	550 - 630	105	60	60	78 x 53	White
Fixed	AU-DDL10160CS	Triac Dim	6	3000 / 4000 / 6500	550 - 630	105	60	60	78 x 53	White
Adjustable	AU-DDL10260CS	Triac Dim	6	3000 / 4000 / 6500	550 - 630	105	60	70	90 x 54	White
Fixed	AU-DDL1019CS	Triac Dim	10	3000 / 4000 / 6500	1000 - 1100	100	60	90	105 x 56	White
	AU-FRLM10EMB	3 Hour Maintained 6.5W Emergency Pack - Downlights								