



Product Description:

LinearPacCWS 4ft IK10 IP66 Anti-Corrosive

The new LinearPacCWS offers up to 180lm/W, market leading efficiency. With colour and wattage switchable technology, the range has been condensed to a minimal number of SKUs whilst still being about to offer a complete range. Designed with the contractor in the mind, the LinearPacCWS has a host of features making super quick and easy to install. Not only does the range come with a generous 5 year warranty, but also a 3 year on-site warranty for everyone's peace of mind.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-ANT1200CWS	14	3000K	2310	120	Grey	Non Dimmable
AU-ANT1200CWS	14	4000K	2520	120	Grey	Non Dimmable
AU-ANT1200CWS	14	6500K	2380	120	Grey	Non Dimmable
AU-ANT1200CWS	18	3000K	2970	120	Grey	Non Dimmable
AU-ANT1200CWS	18	4000K	3240	120	Grey	Non Dimmable
AU-ANT1200CWS	18	6500K	3060	120	Grey	Non Dimmable
AU-ANT1200CWS	24	3000K	3960	120	Grey	Non Dimmable
AU-ANT1200CWS	24	4000K	4320	120	Grey	Non Dimmable
AU-ANT1200CWS	24	6500K	4080	120	Grey	Non Dimmable

Line Drawing	Polar Curve	Colour	
--------------	-------------	--------	--

Feature & Benefits

 Colour switchable between 3000/4000/6500K Wattage switchable for 2ft, 4ft, 5ft, 6ft variants Delivers up to 180lm/W Plug and play module accessories to convert to Emergency and Corridor Microwave Sensor variants, 	 Pre-drilled cable entry points on the back and ends, suitable for 20mm conduit Wide surface bracket rail for flexibility whilst mounting Detachable 4 way loop in/loop out terminal block which can be positioned in 4 locations along the base 	 304 stainless steel fixing clips which can be fixed in the open position DALI converter pack available IP66 rated IK10 rated 	 L70 50,000h 5 year warranty 3 year on-site warranty (registration required) *Terms and conditions apply
---	---	---	---

BESA mounting points on the

back

Product Specs:

with embossed fixing locations

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP66
Lifetime L80 (Hours)	50000hrs	IK Rating	IK10
Width (mm)	96	Length (mm)	1270
Height (mm)	78	Product Type	Linears

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.