



Product Description: LinearPacCWS 6ft IK10 IP66 Anti-Corrosive

The new LinearPacCWS offers up to 180lm/W, market leading efficiency. With colour and wattage switchable technology, the range has been condensed to a minimal number of SKUs whilst still being about to offer a complete range. Designed with the contractor in the mind, the LinearPacCWS has a host of features making super quick and easy to install. Not only does the range come with a generous 5 year warranty, but also a 3 year on-site warranty for everyone's peace of mind.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-ANT1800CWS	27	3000K	4455	120	Grey	Non Dimmable
AU-ANT1800CWS	27	4000K	4860	120	Grey	Non Dimmable
AU-ANT1800CWS	27	6500K	4590	120	Grey	Non Dimmable
AU-ANT1800CWS	35	3000K	5775	120	Grey	Non Dimmable
AU-ANT1800CWS	35	4000K	6300	120	Grey	Non Dimmable
AU-ANT1800CWS	35	6500K	4950	120	Grey	Non Dimmable
AU-ANT1800CWS	45	3000K	7425	120	Grey	Non Dimmable
AU-ANT1800CWS	45	4000K	8100	120	Grey	Non Dimmable
AU-ANT1800CWS	45	6500K	7650	120	Grey	Non Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

- Colour switchable between 3000/4000/6500K
- Wattage switchable for 2ft, 4ft, 5ft, 6ft variants
- Delivers up to 180lm/W
- Plug and play module accessories to convert to Emergency and Corridor Microwave Sensor variants, with embossed fixing locations
- Pre-drilled cable entry points on the back and ends, suitable for 20mm conduit
- Wide surface bracket rail for flexibility whilst mounting
- Detachable 4 way loop in/loop out terminal block which can be positioned in 4 locations along the base
- BESA mounting points on the back
- 304 stainless steel fixing clips which can be fixed in the open position
- DALI converter pack available
- IP66 rated
- IK10 rated
- L70 50,000h
- 5 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP66
Lifetime L80 (Hours)	50000hrs	IK Rating	IK10
Width (mm)	96	Length (mm)	1870
Height (mm)	78	Product Type	Linears
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.