

TECHNICAL DATA

Fluke 302+ CAT III Digital Clamp Meter



Key features

- AC current measurements up to 400 A, handling your everyday electrical maintenance needs
- Comes with the TL75 Hard Point™ Test Lead Set offering the convenience of a test lead and probe in one unit with a variety of connections
- Rugged, easy-to-use digital clamp meter with CAT IV 300 V/CAT III 600 V safety rating

Product overview: Fluke 302+ CAT III Digital Clamp Meter

The Fluke 302+ is a compact, easy-to-use digital clamp meter made to fit the way you work. It is the perfect first-pass troubleshooting tool: small enough to fit in a work bag, tough enough to withstand daily use, and extremely simple to use. All without compromising safety. For everyday applications, where True-RMS accuracy isn't needed, the Fluke 302+ delivers reliable measurements time after time.

Fluke 302+ Additional Features

- The Fluke 302+ CAT III Digital Clamp Meter is more compact, making the use of clamp-type ammeter more flexible and simpler
- Measure AC current up to 400A
- 30 mm large jaw
- High accuracy of 1.8%

- Backlit display
- Two-year warranty

Fluke 302+ Comes with Fluke TL75 Hard Point™ Test Lead Set

- One pair (red, black) of comfort grip probes
- 48 inches (1.22 meter) PVC insulated test leads with right-angle shrouded banana plugs
- Recommended for general purpose measurements
- CAT II 1000 V, 10 A rating
- CAT IV 600 V, CAT III 1000 V only with protective cap

Fluke 302+ Safety Features

- Meets CAT IV 300V/CAT III 600V safety rating

Specifications: Fluke 302+ CAT III Digital Clamp Meter

| Technical Specifications | | |
|--------------------------|-----------------------|------------------|
| AC current | Range | 400.0 A |
| | Accuracy | 1.8% ±5 |
| AC voltage | Range | 400/600 |
| | Accuracy | 1.5% ±5 |
| DC voltage | Range | 400/600 |
| | Accuracy | 1.5% ±5 |
| DC mV range | | - |
| Resistance | Range | 4000 Ω |
| | Accuracy | 1% ±5 |
| Continuity | | ≤ 70 Ω |
| Backlight display | | Yes |
| Data hold | | Yes |
| Size | H x W x D (mm) | 208 x 58.5 x 28 |
| | Jaw size | 30 mm |
| Safety rating | | CAT III 600 V |
| Temperature | | 0 ~ 40 °C |
| Screen refresh rate | | > 2 times / sec. |
| Test leads | | TL75 |
| Battery | | 2 AAA batteries |
| Warranty | | 2 years |

Fluke. *Keeping your world up and running.®*

Fluke (UK) Ltd.
52 Hurricane Way
Norwich, Norfolk
NR6 6JB
United Kingdom
Tel.: +44 (0)20 7942 0708
E-mail: cs.uk@fluke.com
www.fluke.com/en-gb

©2025 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
10/2025

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**