

Luminaires | Fire Rated Downlights

R6™ Colour & Wattage Switchable Fixed Black Baffle Fire Rated Downlight

AU-R63BW/CWS



Photometrics

Wattage	3.5 / 5.5 / 7.5
Lumens	280-660
Beam Angle	60
Colour Temperature	2700 / 3000 / 4000 / 5700
Ra	>90
SDCM	<4

Product Features

Brand	Aurora
IP Rating	65
L80 Hours	50,000
Lifetime Class	L80 B50
Dimmable	Triac
Country of Origin	CN
Barcode	5056102075724

Electrical Specification

Input Voltage Type	AC
Power Factor	0.9

Protection Class	2
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60

Physical Attributes

Finish Colour	White
----------------------	-------

Features

Marketing Feature 1	Certified for solid timber, I-joist, and metal web joist ceilings
Marketing Feature 2	FastRFix connector with LENNEL terminals for ease of installation
Marketing Feature 3	Easy glide soft springs suitable for double plaster board ceilings
Marketing Feature 4	Low profile design for use in shallow ceilings
Marketing Feature 5	Supplied with white IP65 polycarbonate bezel
Marketing Feature 6	CRI90 for optimized colour rendering
Marketing Feature 7	Energy Rating C
Marketing Feature 8	L80B50 50,000hrs
Marketing Feature 9	5 Year Warranty