

# LUMINAIRES - ANTI CORROSIVE

# EN-ANT1240B

Project.....

Fixture Type.....

## **Product Description:**

The IP65 LinearPac<sup>™</sup> LED anti-corrosive has been upgraded up to a market leading 114lm/W providing up to 50% energy savings compared to traditional fluorescent. A highly efficient solution for both interior and exterior applications, it is designed for car parks, service areas, warehouses or retail environments.

| Comments |
|----------|
|----------|

### **Product Image:**




### **Product Features:**

- IP65 vandal resistant polycarbonate body and diffuser
- Efficacy of up to 114 lm/W
- Anti-tamper stainless steel clips supplied as standard
- Clip in gear tray for ease of installation and maintenance
- Multiple drill-out conduit entry points end and rear for quick and easy installation
- Supplied with 2 x IP rated cable glands
- Microwave sensor detection range up to 14 metres
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 15 minutes
- IKO8 impact rating
- 1.0kV surge protection
- 3 year warranty

## Compliance & Approvals:



# Product Dimension:



#### Title

| Input Voltage                | 220/240V AC   |
|------------------------------|---|
| Input Frequency              | 50/60HZ   |
| Operating Temp (Min-<br>Max) | -20-40°C (-4~104°F.)  |
| Dimmable                     | No  |
| Dimensions                   | 1270mm (L) x 118mm (W) x 80mm (H)<br>x mm (OD) x mm (RD) x mm |
| Number of LEDs               | 240   |

## SKU Table and Ordering

| SKU Code          | Colour | lm   | Wattage | Lumens/Watt | Product Type |
|-------------------|--------|------|---------|-------------|--------------|
| EN-ANT1240B/40    | 4000   | 4400 | 40      | 110         | Standard     |
| EN-ANT1240BEM/40  | 4000   | 4400 | 40      | 110         | Emergency    |
| EN-ANT1240BEMR/40 | 4000   | 4400 | 40      | 110         | Emergency    |
| EN-ANT1240BMS/40  | 4000   | 4400 | 40      | 110         | Microwave    |



# 

### Warranty

This product has a warranty period of 3 Yearsfrom the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, and removal of the Q.C. date label; installation in animproper working environment or installation not according to the current edition of the National Electric Code. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Head Office Apex Park 6 Little Burrow Welwyn Garden City AL7 4SW United Kingdom Tel : +44 (0) 1727 83 66 11